

Surge Protective Devices (SPD)

SC-10KVC-277

Description

SC-10KVC-277 is a kind of power supply surge protector suitable for 220V power grid. Used in street lighting, landscape lighting, etc. The shell of the product is made of flame-retardant material, and the product is made of potting glue. It has the characteristics of fire prevention, waterproof and dustproof. Protection grade up to IP67. Installation and application is very convenient, with L, N and PE connection line.

Features

- ◆ The product has full mold protection function. The product has a maximum protection can withstand the impact of 10kV surge voltage.
- ◆ The size of the product is small, 35×26×14mm (excluding the connecting wire).
- ◆ It is a Class III power SPD.
- ◆ Can use series, parallel connection mode, flexible and convenient.
- ◆ Adopt our company's new structure technology manufacturing, break through the conventional structure technology. This process can improve the impact resistance of SPD.
- ◆ Executive standard: IEC/EN:61643-11.
- ◆ Operating Temperature Range: -40℃ to +85℃.



Applications

- ◆ Outdoor and Commercial LED Lighting.
- ◆ Roadway lighting.
- ◆ Traffic lighting.
- ◆ Digital signage.
- ◆ Security power supply.
- ◆ Wash wall lighting.
- ◆ Parking garage lighting.
- ◆ Flood lighting.
- ◆ Tunnel lighting.

Electrical Characteristics

Symbol	Parameter	Value	Unit
Electrical Parameters	Rated Operating Voltage	220	VAC
	Max. Continuous Voltage	277	VAC
	Response Time	25	ns
	Cross-section Area	1	mm ²
Surge Parameters	Nominal Discharge Voltage (1.2/50μs) (Vn)	10	kV
	Maximum Discharge Voltage (1.2/50μs) (Vmax)	20	kV
Voltage Protection Level (Up)	L-N/PE	1.2	kV
	N-PE	1.1	kV

Notes:

1. Nominal discharge voltage surge times: ±15T;
2. Maximum discharge voltage surge times: 1T.

Surge Protective Devices (SPD)

SC-10KVC-277

Application / Inatallation Schematic




Figure 1. Inatallation Schematic




Figure 2. Inatallation Schematic

Notes:

1. The brown wire is Li/Lo wire, Li is the input and Lo is the output, the blue wire is N wire, and the yellow-green wire is the ground wire.
2. After the wire is installed, the product can be tied to the power supply with cable ties. Due to the small volume and weight of the product, it can also be placed freely as shown in Figure 2 of the installation example.

Typical Dimensions



Surge Protective Devices (SPD)

SC-10KVC-277

Packaging Information

Part Number	Quantity
SC-10KVC-277	270 PCS / Box

Warning



- ◆ SOCAY owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property.
- ◆ SOCAY reserves the right to make changes without further notice to any products herein.
- ◆ SOCAY makes no warranties, representations or warranties as to the fitness of its products for any particular purpose, and disclaims any liability.
- ◆ The parameters provided in the SOCAY datasheet specification may vary from application to application, and the actual performance may vary over time. All operating parameters must be verified by the customer's technical expert before application.
- ◆ Any and all responsibilities and liabilities are disclaimed if any item under this notice of warning is not complied with.